




# CAP 1 Slim design 90°

## Technical Data


Caractéristiques techniques / Technische Daten

	ER-8 / 5 mm
<b>R.P.M max</b>	6.000
	5 Kg
	1:1
<b>KW</b>	1 Kw
<b>Nm max</b>	3 Nm
<b>Rotation</b>	in = out (C) in ≠ out (A-B)

**L / H**

Other measures under request

Autres mesures sur demande  
Weitere Maßnahmen auf Anfrage




**MADAULA**  
creative solutions

<b>L</b>	A	50
	B	75
	C	100

Taper Cône / Kegel	Size Taille / Größe	H	S
<b>DIN 69871 / 2080</b>	40/50	65/80	40
<b>CAT</b>	40/50	65/80	40
<b>MAS-BT</b>	40/50	65/80	40/50
<b>HSK</b>	63/100	65/80	40/50
<b>CAPTO</b>	C6/C8	65/80	40/50
<b>KM</b>	63/100	65/80	40/50

## Standard Equipment

Standard / Standard



## Optional Equipment

Optionel / Option

### Stop Block

Bloc d'arrêt / Anschlag-Block

See page 51



### Collets

Pincen / Spannzangen

See page 52



### Coolant through index pin

Arrosage par le doigt d'indexage / Kühlmittelzufuhr durch bolzen

bar/psi max 12/175